

WHAT IS CLAIMED IS:

1. A blow-molded table, comprising a table board, and two opposite support units each foldably mounted on a bottom of the table board, wherein:

the bottom of the table board is formed with a receiving space; and

5 each of the two support units is mounted in the receiving space of the table board and includes a support stand pivotally mounted on either one of two ends of the table board, and a support member pivotally mounted on a mediate of the table board and pivotally connected with the support stand.

2. The blow-molded table in accordance with claim 1, wherein the
10 receiving space of the table board has two opposite sides each provided with a support tube which is secured on the table board by a plurality of screws.

3. The blow-molded table in accordance with claim 1, wherein the support stand of each of the two support units is provided with an auxiliary reinforcement member.

15 4. The blow-molded table in accordance with claim 1, wherein the support member of each of the support units includes a support bar having a first end pivotally mounted on the mediate portion of the table board, and an extension bar having a first end pivotally mounted on a second end of the support bar and a second end pivotally mounted on the support stand.

20 5. The blow-molded table in accordance with claim 4, wherein the support stand of each of the two support units is provided with an auxiliary reinforcement member having a mediate portion formed with a substantially

C-shaped holder clamped on the support bar of the support member when the support member and the support stand are folded, so that the support member is combined with the support stand.

6. The blow-molded table in accordance with claim 4, wherein the
5 support bar is substantially T-shaped.

7. The blow-molded table in accordance with claim 4, wherein the extension bar is substantially V-shaped.

8. The blow-molded table in accordance with claim 1, wherein the support stands of the two support units are in alignment with each other.

10 9. The blow-molded table in accordance with claim 4, wherein the support bars of the two support units are juxtaposed to each other.

10. The blow-molded table in accordance with claim 1, wherein the receiving space of the table board is formed with a plurality of receiving recesses for receiving the support stand and the support member of each of the
15 support units when being folded.

11. The blow-molded table in accordance with claim 4, wherein the support bars of the two support units are spaced from each other.

12. The blow-molded table in accordance with claim 1, wherein the support stands of the two support units are arranged in a staggered manner.

20